

IDENTIFICATION

Product Identifier: SUPERIORE DEGREASER

Product Code: FL1062


Recommended use of chemical and restrictions on use: Solvent Degreaser

HAZARD IDENTIFICATION

DANGEROUS GOODS: Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. • **FLAMMABLE LIQUID CLASS 3.2**

GHS Classification: This product is classified as hazardous under the Globally Harmonised System (GHS) and Australian Work Health and Safety regulations.

- Aspiration Hazard: Category 1
- Eye Damage/Irritation: Category 2A
- Skin Corrosion/Irritation: Category 2
- Flammable Liquids: Category 3
- Acute Toxicity – Dermal: Category 4
- Acute Toxicity – Oral: Category 4
- STOT (Specific Target Organ Toxicity) Single Exposure: Category 3 (narcotic)



Pictogram: Health Hazard (causes damage overtime), Exclamation Mark, Dangerous for the environment, Corrosive, Flammable

Signal Word (s) DANGER

ASV Euro Car Parts Pty. Ltd.

Unit 2 / 2 Christina Road,
Villawood NSW 2163
Australia
Tel: 13 88 00

Hazard Statement: H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation. H315 Causes skin irritation.

H336 May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways.

Harmful if swallowed. Harmful in contact with skin. May cause drowsiness or dizziness.

General Statement: Keep out of reach of children. Read label before use.

Safety Directions: Wear eye protection/face protective gloves. Wash hands and skin thoroughly after use.

FIRST AID:

INGESTION: Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. Do NOT attempt to give anything by mouth to an unconscious person. Rinse mouth thoroughly with water immediately. Give water to drink. If vomiting occurs, give further water to achieve effective dilution. Seek medical advice (e.g. doctor).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. If eye irritation persists: Get medical advice/attention.

SKIN CONTACT: Immediately flush skin with soap and plenty of water. Remove contaminated clothing and wash before re-use. Seek medical advice if symptoms persist.

INHALATION: Remove to fresh air, get medical attention if symptoms occur.

PREVENTION: Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/tools/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash contaminated skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

INGREDIENTS

NAME	CAS NUMBER	PROPORTION
Solvent Naphtha	64742-89-8	> 90- <100 %
Ingredients determined not to be hazardous Not required to 100%	Not required	to 100%

FIRE-FIGHTING MEASURES

Fire Hazard: Carbon monoxide may be evolved during a fire. Will float and can be reignited on surface water. Vapour is heavier than air, can spread along ground and distant ignition is possible

Extinguishing Media: Foam, dry chemical powder or carbon dioxide. 22/04/2019 SDS 4/8 Use water spray/fog to cool containers. Do not use water in a jet.

Fire Fighting: Use an extinguishing media for surrounding fires. Keep containers exposed to extreme heat cool with water spray. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion or decomposition.

Flash Point: <60.5°C

ACCIDENTAL RELEASE MEASURES

Cleanup: Avoid direct contact with spilled material. If safe, stop the leak at its source. Eliminate ignition sources such as open flames or electrical equipment. Use non-combustible absorbents like sand or soil to contain the spill and prevent it from entering drains or waterways. Avoid using flammable materials like sawdust. Take precautions against static discharge by ensuring proper bonding and grounding of equipment. Once absorbed, transfer the material to a labelled chemical waste container for safe disposal.

Minor Spills: Remove all ignition sources. For small spills (<1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Use an appropriate absorbent material to pick up residue and dispose of safely.

Major Spills: Keep the spill away from drains and waterways. Evacuate the area and keep unprotected individuals at a safe distance. Immediately contact emergency services (e.g. Fire Brigade). Wear full protective gear, including eye and face protection, and ensure all skin is covered. Stay upwind and avoid direct contact with the substance. If safe to do so, stop the leak at its source. Eliminate ignition sources such as open flames or electrical equipment. For larger spills (greater than one drum), use appropriate equipment like a vacuum truck to transfer the material to a salvage tank for recovery or disposal. Do not flush residues with water. Use suitable absorbent materials to clean up and dispose of waste safely. Notify relevant authorities if required.

HANDLING AND STORAGE

Handling: Avoid breathing in fumes or direct contact with the material. Always work in well-ventilated areas and use personal protective equipment as needed. Handle open containers carefully and avoid splashing. Prevent the substance from entering drains or waterways. If contamination occurs, remove affected clothing and wash thoroughly before eating, drinking, or smoking. Store away from strong oxidizing agents and follow workplace exposure limits. Take precautions to prevent static discharge by ensuring proper grounding and bonding of equipment.

Storage: Electrostatic charges may build up during transfer and could ignite flammable vapours. Take precautions to prevent static discharge by ensuring proper bonding and grounding of all equipment. Store flammable materials in approved areas that meet local safety regulations. Use bunded tanks to contain leaks and prevent soil or water contamination. Only trained and properly equipped personnel should clean or inspect storage tanks. Keep the product away from oxidizing agents and follow all relevant safety protocols.

EXPOSURE CONTROLS & PERSONAL PROTECTION

Worksafe Australia has set an exposure limit for this product.

A TWA of 300 mg/m³ TWA (8hr) is recommended.

Appropriate Engineering Controls: Ensure the area is well ventilated to prevent the buildup of fumes or mist. Maintain air concentrations below recommended exposure limits. Avoid generating aerosols or inhaling vapours. Keep containers sealed when not in use to minimize exposure. Use personal protective equipment as needed and follow workplace safety guidelines to reduce risk.

Personal Protective Equipment: Not required for normal use. When handling large amounts use OVERALLS/APRONS, SAFETY SHOES, SAFETY GLASSES/ contact lenses, GLOVES.

STABILITY & REACTIVITY

This product is chemically stable under normal conditions of use. Avoid exposure to heat, sparks, open flames, and other ignition sources. Keep away from incompatible materials such as strong

oxidizing agents. During combustion or thermal degradation, hazardous decomposition products may be released, including carbon monoxide, carbon dioxide, and other organic compounds. These emissions depend heavily on the conditions and may include a complex mixture of airborne solids, liquids, and gases. Follow proper storage and handling procedures to minimize risk.

TOXICOLOGICAL INFORMATION

Ingestion of this product may be harmful and can irritate the digestive tract, potentially causing nausea and vomiting. If swallowed or vomited, there is a risk of aspiration into the lungs, which may lead to chemical pneumonitis. Inhalation of vapours or mist may irritate the respiratory system. High concentrations can cause symptoms such as headache, dizziness, nausea, vomiting, or drowsiness. Prolonged or repeated skin contact may lead to defatting and drying, resulting in irritation or dermatitis. Exposure to liquid or vapours may irritate the eyes, causing pain, tearing, redness, and swelling. Chronic exposure through skin contact or inhalation may lead to persistent irritation or, in severe cases, narcosis. Use appropriate personal protective equipment and follow safety guidelines to minimize risk.



ECOLOGICAL INFORMATION

This product is expected to be toxic to aquatic organisms and may cause long-term harm to the aquatic environment. Avoid release into waterways. No specific data is available on persistence or biodegradability. The substance is slightly miscible with water and may spread slowly in aquatic systems. Handle and dispose of responsibly to minimize environmental impact.

DISPOSAL INFORMATION

Dispose of waste according to applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

TRANSPORT INFORMATION – LABELS REQUIRED

ADG	 <p>Classified as Dangerous Goods.</p>
IMDG Marine Pollutant	 <p>Yes</p>

LAND TRANSPORT (ADG)

UN Number	UN 1268
Shipping Name	PETROLEUM DISTILLATES, N.O.S.(Solvent Naptha (Light Aliphac))
HAZCHEM Code	3Y
Special Provisions	TP1, TP8, TP28
Packing Group	III
Segregation	Segregation Class 3 – Flammable liquid shall not be loaded in the same vehicle or packed in the same freight container with: Class 1, Explosives Class 2.1, Flammable Gases, if both the Class 3 and Class 2.1 dangerous goods are in bulk Class 2.3, Toxic Gases Class 4.2 Spontaneously Combustible Substances Class 5.1 Oxidising Agents and Class 5.2, Organic Peroxides Class 6 Toxic Substances (where the flammable liquid is nitromethane) Class 7 Radioactive Substances. Foodstuff empties.

The information contained herein is subject to change without notification. Typical properties may vary slightly.

ASV Euro Car Parts Pty. Ltd.

 Unit 2 / 2 Christina Road,
 Villawood NSW 2163
 Australia
 Tel: 13 88 00