

IDENTIFICATION

Product Identifier: FLUSSO BENZINA FUEL TREATMENT & INJECTOR CLEANER

Product Code: FL1112 & FL1113, FL1114

Recommended use of chemical and restrictions on use: Fuel treatment

HAZARD IDENTIFICATION

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

GHS Classification: This product is classified as hazardous under the Globally Harmonised System (GHS) and Australian Work Health and Safety regulations.

- Serious Eye Damage/Irritation Category 1
- Skin Irritation Category 2
- Specific Target Organ Toxicity 3 (respiratory)
- Acute Toxicity Category 4 (Inhalation)
- Acute Toxicity Category 4 (Skin)
- Acute Toxicity Category 4 (Ingestion)
- Flammable Liquids Category 4
- Acute Aquatic Toxicity - Category 2



Pictogram: Corrosive, Exclamation Mark

Signal Word (s) WARNING

Hazard Statement: Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. Combustible liquid. Toxic to aquatic life.

General Statement: Keep out of reach of children. Read label before use.

ASV Euro Car Parts Pty. Ltd.

Unit 2 / 2 Christina Road,

Villawood NSW 2163

Australia

Tel: 13 88 00



FLUSSO BENZINA

FUEL TREATMENT & INJECTOR CLEANER

Safety Data Sheet

PRODUCT CODE: FL1112 (350ML), FL1113 (5L), FL1114 (20L)

Safety Directions: Wear eye, face and protective gloves. Wash hands and skin thoroughly after use. Avoid release to the environment.

NAME	CAS NUMBER	PROPORTION
2-Butoxyethanol	111-76-2	> 60 % w/w
C12-C15 alcohol ethoxylate	68131-39-5	10 – 30 % w/w
Ingredients determined to be non-hazardous at concentrations present	various	to 100%

FIRST AID:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before use. This material can be absorbed through the skin with resultant toxic effects.

INGESTION: Do not induce vomiting. Rinse the mouth thoroughly with water. Provide water to drink. Seek medical attention immediately.

ADVICE TO DOCTOR: Treat symptomatically. Show this SDS to the medical practitioner.

FIRST AID MEASURE: For advice, contact a Poisons Information Centre (Phone eg. Australia 131 126; New Zealand 0 800 764 766) or a doctor.

STORAGE & DISPOSAL: Dispose of contents in accordance with local regulations.

INGREDIENTS

FIRE-FIGHTING MEASURES

Fire Hazard: Non-flammable liquid. However, once the water component evaporates, the remaining material may be combustible.

Extinguishing Media: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Hazards from Combustion Products: Avoid contact with oxidising agents, as this may result in a fire or explosion hazard. Decomposes when heated, potentially releasing toxic fumes including carbon dioxide, nitrogen oxides, and other typical combustion products of organic materials.

ASV Euro Car Parts Pty. Ltd.

Unit 2 / 2 Christina Road,
Villawood NSW 2163
Australia
Tel: 13 88 00



Specific Methods: Keep containers cool using water spray. Firefighters should wear self-contained breathing apparatus and appropriate protective clothing if there is a risk of exposure to vapours or combustion products.

ACCIDENTAL RELEASE MEASURES

Emergency Procedures: Eliminate all potential ignition sources and evacuate any unprotected personnel from the area. Wear appropriate protective equipment to avoid skin and eye contact and prevent inhalation of vapours.

Spills & Disposal: Contain the spill and stop it from entering drains or waterways. If any contamination of sewers or water systems occurs, immediately notify local emergency services.

HANDLING AND STORAGE

Handling: Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements. This material is a Scheduled Poison S6 and must be stored, maintained and used in accordance with the relevant regulations.

Storage: Store in a cool, dry, well-ventilated place. Store away from sources of heat or ignition. Store away from foodstuffs. Do not store in aluminium or galvanised containers nor use die-cast zinc or aluminium bungs; steel bungs should be used. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

EXPOSURE CONTROLS & PERSONAL PROTECTION

Occupational exposure limit values: National Occupational Exposure Limits, as published by SAFEWORK AUSTRALIA:

Time-weighted Average (TWA): None established for product.

- 2-Butoxyethanol: 20ppm, (96.9 mg/m³)

Short Term Exposure Limit (STEL): None established for product.

- 2-Butoxyethanol: 50 ppm, (242 mg/m³)

Appropriate Engineering Controls: Use good occupational practice.

Personal Protective Equipment: Use safety glasses with a full face shield when handling larger quantities or cleaning spills, and avoid contact lenses; wear impervious gloves such as butyl rubber, latex, neoprene, PVC or nitrile, along with chemical-resistant clothing like an apron, sleeves, boots, and buttoned cotton overalls; and if ventilation is inadequate, use an approved respirator with a vapor or mist filter, ensuring all protective equipment meets the relevant Australian/New Zealand standards.

STABILITY & REACTIVITY

This substance reacts with strong oxidising agents and should be kept away from heat, ignition sources, and open flames, as excessive heat can speed up oxidative breakdown. Contact with aluminium or aluminium alloys may produce alcoholates and release hydrogen, and exposure to air may lead to peroxide formation. It is incompatible with strong oxidisers, aluminium and its alloys, copper and copper alloys, neoprene, natural rubber, bases, amines, ammonia, and acid chlorides. Hazardous decomposition may produce oxides of carbon.

TOXICOLOGICAL INFORMATION

If used as directed, this product shouldn't cause harm. Breathing in vapours may irritate your nose and throat, and high levels can make you feel dizzy or drowsy. It can irritate and dry out your skin, and repeated contact may cause dermatitis. Getting the concentrate in your eyes can cause strong irritation or even damage. Swallowing it may cause nausea, vomiting, and drowsiness, and vomiting could lead to material entering the lungs. Long-term or repeated exposure may affect the liver, kidneys, or red blood cells. There is no evidence it causes cancer, genetic damage, reproductive harm, skin or breathing allergies, or aspiration hazards.

ECOLOGICAL INFORMATION

This product has moderate acute aquatic toxicity (Category 2), with an LC50 of approximately 8.2–8.4 mg/L, while other components show low toxicity with LC50 values above 100 mg/L and are therefore not classified as hazardous. The surfactants present are readily biodegradable (AS4351), are not expected to bioaccumulate, and are highly mobile in the environment, tending to move

ASV Euro Car Parts Pty. Ltd.

Unit 2 / 2 Christina Road,
Villawood NSW 2163
Australia
Tel: 13 88 00



FLUSSO BENZINA

FUEL TREATMENT & INJECTOR CLEANER

Safety Data Sheet

PRODUCT CODE: **FL1112 (350ML), FL1113 (5L), FL1114 (20L)**

into water systems. Despite its biodegradability, the product is still toxic to aquatic life, so it must not be released into waterways.

DISPOSAL INFORMATION

Dispose of waste according to applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

The information contained herein is subject to change without notification. Typical properties may vary slightly.

ASV Euro Car Parts Pty. Ltd.
Unit 2 / 2 Christina Road,
Villawood NSW 2163
Australia
Tel: 13 88 00

