

**DESCRIPTION**

MAX-POTENZA DOT 3 is a high-performance premium grade synthetic brake fluid suitable for brake and clutch systems in automotive, commercial, mining, and heavy-duty applications. It is suitable for disc or drum brakes.

**DIRECTIONS**

1. Flush Used Fluid from System.
2. Clean System Components to Remove Contaminants.
3. Add Fluid Following OEM Recommendations.
4. Reseal MAX-POTENZA Dot 3 Immediately to Prevent Contamination

**SPECIFICATIONS**

MAX-POTENZA DOT 3 meets the following specifications.

AS 1960-2005 Grade 1	ISO 4925 Class 3
FMVSS 116 DOT 3	SAE J 1704

**RECOMMENDED APPLICATIONS**

Automotive	Drilling	Mining
Agricultural	Earth Moving	Motorcycle
Construction	Light Commercial	On & Off Highway Transport

**PRODUCT CODE / AVAILABLE COLOURS:**

Available	Pack Size	Colour	Pack
FL1250	20L	Amber	Cube

**TECHNICAL DATA**

CHARACTERISTIC	RESULT
<b>Appearance</b>	Mobile Liquid
<b>Density at 25°C</b>	1.07
<b>Colour</b>	Amber
<b>Odour</b>	Characteristic
<b>pH</b>	7.5 – 8.5
<b>Solubility</b>	Miscible
<b>Flammable</b>	Not flammable
<b>Freezing Point</b>	-40°C
<b>Boiling Point</b>	230-260°C
<b>Volatile Organic Compounds</b>	Not Available
<b>DG Class</b>	Non-Dangerous Goods
<b>Hazardous</b>	Category 2A

The information contained herein is subject to change without notification. Typical properties may vary slightly.