

DESCRIPTION

Forte Classica 10W-30 is a synthetic technology lubricant developed for the most recent requirement of petrol and diesel engines fitted in light commercial and passenger cars. It meets all current industry standard requirements of domestic car manufacturers recommending API SN.

FEATURES AND BENEFIT

Forte Classica 10W-30 is formulated to provide total engine protection and offers both cleanliness and durability with an excellent resistance to degradation. The product maintains good fluidity at low temperatures for cold starts and requires less frequent top ups due to low oil consumption.

APPLICATIONS

Forte Classica 10W-30 performs under the most difficult operating conditions on highways and congested city traffic alike. Recommended for all petrol and diesel engines (multi-valve and turbo types) turbo-charged or naturally aspirated in passenger cars.

SPECIFICATIONS

Meets the requirements of:

- API SN /CF
- ACEA A3/B4
- MB 229.3
- FIAT 9.55535-G2
- Renault RN 0700, RN 0710
- VW 502 00, VW 505
- ILSAC GF-5

TECHNICAL DATA

CHARACTERISTIC	TEST METHOD	RESULT
Physical Appearance	Visual	Bright and Clear
Viscosity @ 40°C cSt	ASTM D 445	71.45
Viscosity @ 100°C cSt	ASTM D 445	11.50
Viscosity Index	ASTM D 2270	155
Total base Number	ASTM D 2896	8.2
Pour Point °C	ASTM D 97	-36
Flash Point °C	ASTM D 92	224
CCS cp	ASTM D5293	3872@-25°C

The Forte and ASV logos are trademarks of Euro Car Parts Pty Ltd. The Verus logo is a trademark of Chematek SpA. Data is based on standard laboratory tests and provided as a guide only. Normal manufacturing variations that do not affect performance may occur.

This data sheet is accurate as of the print date, but no express or implied warranties are given regarding its accuracy or completeness. Users must refer to the latest version, assess suitability for their application, and comply with relevant laws. Material Safety Data Sheets are available and should be consulted for safe handling, storage, and disposal. Neither Euro Car Parts Pty Ltd, Chematek SpA, nor their subsidiaries accept liability for misuse, failure to follow recommendations, or inherent material hazards. Contact our local representative for further information.