

# Energia 5W-30 c2/c3, sp (sn/cf)

**Synthetic Technology** 

PRODUCT CODE: xx053001

### **DESCRIPTION**

Forte Energia 5W-30 C2/C3, SP (SN/CF) is a Mid-SAPS synthetic technology lubricant formulated to help deliver unparalleled engine protection and excellent fuel economy whilst keeping your engine clean and new. Forte Energia is perfect for all types of vehicles anywhere in the world and has the performance reserve to protect when conventional engine oils cannot. It is formulated to meet requirements for some of the world's finest performance vehicles: Mercedes-Benz AMG, Porsche, and Aston Martin.

#### **FEATURES AND BENEFIT**

Forte Energia 5W-30 C2/C3, SP (SN/CF) has a low viscosity, new generation synthetic technology synthetic formulation that helps to increase engine efficiency and improve fuel economy, whilst providing outstanding overall engine protection.

Key features and potential benefits include:

- Designed to clean up sludge left behind in your engine
- Outstanding low temperature capabilities
- Low viscosity, helps improve fuel economy benefits
- Outstanding thermal and oxidation stability
- Longer drain interval in comparison to other conventional based products

#### **APPLICATIONS**

Forte Energia 5W-30 C2/C3, SP (SN/CF) is designed for use in modern passenger cars and lightduty commercial vehicles equipped with gas exhaust after-treatment systems such as DPF.

### **SPECIFICATIONS**

Meets the requirements of:

- API SP (SN/CF)
- ILSAC GF-6A
- ACEA C2/C3
- GM DEXOS 2
- MB 229.51

- FIAT 9.55535-G2, 9.55535-S2
- VW 502 00, VW 505 00
- Ford WSS-M2C946-A, WSS-M2C946-B1, WSS-M2C961-A
- PSA B71 2290



**ASV Euro Car Parts Pty. Ltd.** 

Distribution Centre
Unit 2 / 2 Christina Road,
Villawood NSW 2163
Australia
Tel: 13.88.00

Tel: 13 88 00 www.fortelubricants.com.au





# Energia 5W30 c2/c3, sp (sn/cf)

**Synthetic Technology** 

PRODUCT CODE: xx053001

#### **TECHNICAL DATA**

CHARACTERISTIC	TEST METHOD	RESULT
Physical Appearance	Visual	Bright and Clear
Density @ 15 °C, gm/cm3	ASTM D4052	0.859
Viscosity @ 40°C cSt	ASTM D 445	57
Viscosity @ 100°C cSt	ASTM D 445	10.2
Viscosity Index	ASTM D 2270	169
Pour Point °C	ASTM D 97	-28
Flash Point °C	ASTM D 92	228

The Forte and ASV logos are trademarks of Euro Car Parts Pty Ltd. The Verus logo is a trademark of Chematek SpA. Data is based on standard laboratory tests and provided as a guide only. Normal manufacturing variations that do not affect performance may occur.

This data sheet is accurate as of the print date, but no express or implied warranties are given regarding its accuracy or completeness. Users must refer to the latest version, assess suitability for their application, and comply with relevant laws. Material Safety Data Sheets are available and should be consulted for safe handling, storage, and disposal. Neither Euro Car Parts Pty Ltd, Chematek SpA, nor their subsidiaries accept liability for misuse, failure to follow recommendations, or inherent material hazards. Contact our local representative for further information.





Distribution Centre
Unit 2 / 2 Christina Road,
Villawood NSW 2163
Australia
Tel: 13.88.00

Tel: 13 88 00 www.fortelubricants.com.au

