

Energia 5W-40 c3, sn/cf

Full Synthetic

PRODUCT CODE: xx054001

DESCRIPTION

Forte Energia 5W-40 C3, SN/CF is the most advanced performance synthetic engine oil designed to provide ultimate cleaning power, wear protection and overall performance. Forte Energia is perfect for all types of vehicles anywhere in the world and has the performance reserve to protect when conventional engine oils cannot. It is formulated to meet requirements for some of the world's finest performance vehicles: Mercedes-Benz AMG, Porsche, and Aston Martin.

FEATURES AND BENEFIT

Forte Energia 5W-40 C3, SN/CF is made with a proprietary blend of ultra-high performance top synthetic base stocks. Its wide viscosity range provides unsurpassed levels of protection, fuel savings and the best overall smooth driving experience. It keeps engines starting in extreme cold and cleans deposits, sludge and varnish often formed in high temperature operating conditions. Exceeding most of the global industry standards and the major leading builder requirements is the cornerstone of the performance reserve that lets Forte Energia 5W-40 keep performing well after conventional oils cannot.

APPLICATIONS

Forte Energia 5W-40 C3, SN/CF is recommended for all types of modern vehicles, especially highperformance turbo-charged, supercharged petrol and diesel multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.

SPECIFICATIONS

Meets the requirements of:

- API SN/CF
- ACEA C3
- GM DEXOS 2
- MB 229.51
- BMW LL-04

- PORSCHE A40
- FIAT 9.55535-S2
- VW 505 00, VW 505 01
- Ford WSS-M2C917-A



ASV Euro Car Parts Pty. Ltd.

Distribution Centre
Unit 2 / 2 Christina Road,
Villawood NSW 2163
Australia

Tel: 13 88 00 www.fortelubricants.com.au





Energia 5W-40 C3, SN/CF

Full Synthetic

PRODUCT CODE: xx054001

TECHNICAL DATA

CHARACTERISTIC	TEST METHOD	RESULT
Physical Appearance	Visual	Bright and Clear
Density @ 15 °C, gm/cm3	ASTM D4052	0.859
Viscosity @ 40°C cSt	ASTM D 445	77.25
Viscosity @ 100°C cSt	ASTM D 445	13.3
Viscosity Index	ASTM D 2270	175
Pour Point °C	ASTM D 97	-45
Flash Point °C	ASTM D 92	228

The Forte and ASV logos are trademarks of Euro Car Parts Pty Ltd. The Verus logo is a trademark of Chematek SpA. Data is based on standard laboratory tests and provided as a guide only. Normal manufacturing variations that do not affect performance may occur.

This data sheet is accurate as of the print date, but no express or implied warranties are given regarding its accuracy or completeness. Users must refer to the latest version, assess suitability for their application, and comply with relevant laws. Material Safety Data Sheets are available and should be consulted for safe handling, storage, and disposal. Neither Euro Car Parts Pty Ltd, Chematek SpA, nor their subsidiaries accept liability for misuse, failure to follow recommendations, or inherent material hazards. Contact our local representative for further information.





Distribution Centre Unit 2 / 2 Christina Road, Villawood NSW 2163 Australia

www.fortelubricants.com.au

Tel: 13 88 00

