

DESCRIPTION

Forte Energia 5W-30 SP GF-6A is a Mid-SAPS premium quality, fully synthetic lubricant formulated to deliver unparalleled engine protection and excellent fuel economy benefits whilst keeping your engine clean and new. Offering protection for critical engine parts, the oil allows the maximum oil change intervals indicated by the manufacturers when operating under optimum conditions. Forte Energia 5W-30 SP GF-6A meets or exceeds the requirements of the industry's toughest standards and outperforms our conventional and synthetic technology oils

FEATURES AND BENEFIT

Forte Energia 5W-30 SP GF-6A is designed with a proprietary blend of high-performance synthetic base stocks and precisely balanced component additive system. The low viscosity, new generation synthetic formulation that helps to increase engine efficiency and improve fuel economy, whilst providing outstanding overall engine protection.

Key features and potential benefits include:

- Designed to clean up sludge left behind in your engine
- Outstanding low temperature capabilities
- Low viscosity, advanced top synthetic formula helps improve fuel economy benefits
- Outstanding thermal and oxidation stability
- Longer drain interval in comparison to other conventional based products

APPLICATIONS

Forte Energia 5W-30 SP GF-6A is designed for all types of modern vehicles, especially high performance turbo-charged, supercharged petrol and diesel multi-valve fuel injected engines found in passenger cars, SUVs and light commercial vehicles.

SPECIFICATIONS

Meets the requirements of:

- API SP
- ILSAC GF-6A
- ACEA C2/C3
- GM DEXOS 2
- MB 229.51
- BMW LL-04
- FIAT 9.55535-G2, 9.55535-S2
- VW 502 00, VW 505 00
- Ford WSS-M2C946-A, WSS-M2C946-B1, WSS-M2C961-A
- PSA B71 2290

TECHNICAL DATA

CHARACTERISTIC	TEST METHOD	RESULT
Physical Appearance	Visual	Bright and Clear
Density @ 15 °C, gm/cm ³	ASTM D4052	0.859
Viscosity @ 40°C cSt	ASTM D 445	62.5
Viscosity @ 100°C cSt	ASTM D 445	11.0
Viscosity Index	ASTM D 2270	172
Pour Point °C	ASTM D 97	-45
Flash Point °C	ASTM D 92	228

The Forte and ASV logos are trademarks of Euro Car Parts Pty Ltd. The Verus logo is a trademark of Chematek SpA. Data is based on standard laboratory tests and provided as a guide only. Normal manufacturing variations that do not affect performance may occur.

This data sheet is accurate as of the print date, but no express or implied warranties are given regarding its accuracy or completeness. Users must refer to the latest version, assess suitability for their application, and comply with relevant laws. Material Safety Data Sheets are available and should be consulted for safe handling, storage, and disposal. Neither Euro Car Parts Pty Ltd, Chematek SpA, nor their subsidiaries accept liability for misuse, failure to follow recommendations, or inherent material hazards. Contact our local representative for further information.